







ELITECH LINE EL991E

TYPE	Warewasher
LINE	ELITECH LINE
BASKET	600x670
SIZE	1445x855x2015/2290h

The EL991E warewasher is the answer for anyone who has to effectively wash objects measuring up to 575x645x825(h)mm inside its two baskets, thanks to the two wash pumps and two rinse pumps. It is suitable for washing baking trays, pots of various kinds, mixing bowls, utensils and even 52 dishes at each cycle as it is equipped with two baskets with a maximum productivity of 60 baskets/hour (3120 dishes/hour). The work height and the counterbalanced door facilitate loading while the double walls improve thermal-acoustic insulation. The rounded moulded tank with integral filters ensures maximum hygiene and perfect draining.

The dishwashers of the ELITECH line ensure maximum performance thanks to the standard Acquatech System which, through an atmospheric boiler and rinse pump, maintains constant temperature and pressure and optimum water consumption. Elitech ensures a sanitising rinse cycle and proves to be the perfect choice for canteens, nursing homes, pastry shops, bakers and butchers where compliance with HACCP rules is essential. For anyone seeking perfectly sparkling glasses, it is possible to connect a Reverse Osmosis System which purifies water and reduces detergent and rinse-aid consumption, ensuring excellent results and perfect glasses without the need for hand drying. The innovative UNIKO tempered glass touch screen display makes any operation simple and intuitive, from the choice of the most suitable wash cycle to its progress control, as well as constantly monitor the status of the dishwasher with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician through the Wi-Fi IKLOUD control system that offers the possibility of remotely changing the dishwasher parameters and resolving the situation

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations that need to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the hot water from the boiler, preventing limestone from building up inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all of the components in the front for easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.

FHI C ∈ ⊕

♦WRAS










DISTRIBUTED FEATURE	ELITECH LINE EL 001E
DISHWASHERS FEATURES	ELITECH LINE EL991E
Dimensions - (mm) L - P - H	1445x855x2015/2290h
n° baskets/hour - (+55°C)	Max 60
Height pot max	830mm
LT bread basket	2 x 100
Trays	GN1/1 - 60x40 GN2/1 - 60x80
Tank heating element - Tank capacity	9,0 kW - 100lt
Boiler heating element - Boiler capacity	9,0kW - 20,8lt
Washing pump	2 x 2,0kW / 2 x 2,7Hp
Total power input / Current	13,0kW / 32A
Standard input voltage	400V3N+T 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	4,0-5,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Acquatech system rinse	si
ACCESSORI	
8 division cutlery insert	2
Integral tank filter	1 + 1
Inox basket dim.600x670x100mm	2
Basket for trays with 5 compartments	2
OPTION	
UNIKO touch display with IKLOUD Wi-Fi control	•
Booster pump kit 0,5Hp	-
Drain pump kit 32W	•
Boiler heating element 4,5kW	•
Boiler heating element 5,4kW	•
Reverse osmosis system	-
Kit 4 Stainless steel feet 50-70mm	-
SOFT Door Opening/Closing System	•
Energy Pro Green	•
Optional Installabile, Optional not installable	

EL991E



WRAS APPROVED PRODUCT

