







CUBE LINE C327

| TYPE | Glasswasher |
|--------|--------------|
| LINE | CUBE LINE |
| BASKET | 350x350 |
| SIZE | 420x485x660h |

Reliability and ease of use: these are the key words of the **CUBE** line. The **ADVANCE** panel is the real strength of the **CUBE** line thanks to its **4** washing cycles and one automatic drain cycle (with drain pump installed). On the control panel you can easily view the tank and boiler temperature, the messages of the **Self-diagnosis** system, the **Scheduled Maintenance** warning and the **intelligent Start button**, which changes colour to always display the restrictions the prospection and experience and draining times, the washing and ringing temperatures and the relative Thormastons erviced for oppuring setting and controlling the rinsing and draining times, the washing and rinsing temperatures and the relative Thermostops, crucial for ensuring excellent washing results.

The C327 model, available with round basket or with square basket, is the most appropriate choice to wash cups, saucers and glasses in a very tight space, using a single 120-second standard cycle in the UP version.

The standard double electric rinse-aid and detergent dispenser ensures maximum hygiene at each wash cycle with great savings: the moulded washing and rinsing arms ensure reliability and durability. The bodywork is made entirely of AISI 304 steel and has been designed with all of the components in the front for easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.

EH[**C** €

♦WRAS









| DISHWASHERS FEATURES | CUBE LINE C327 |
|--|-----------------|
| Dimensions - (mm) L - P - H | 420x485x660h |
| n° baskets/hour - (+55°C) | 30 |
| Height glass max | 240mm |
| Tank heating element - Tank capacity | 2,6kW - 13lt |
| Boiler heating element - Boiler capacity | 2,5kW 3,2lt |
| Washing pump | 0,19kW / 0,25Hp |
| Total power input / Current | 2,79kW / 16A |
| Standard input voltage | 230V 50Hz |
| Recommended inlet water temperature | +55°C |
| Water hardness | 7÷10 °f |
| Water consumption per cycle (inlet suggested pressure 2 BAR) | 2,0lt |
| Adjustable detergent and rinse-aid dispenser | ELECTRIC |
| ACCESSORI | |
| Basket for glasses dim.350x350x150mm | 2 |
| Basket for glasses Ø350mm | -0 |
| Saucer holder 12 pieces | 1 |
| Cutlery insert | 1 |
| OPTION | |
| UNIKO touch display with IKLOUD Wi-Fi control | - |
| Booster pump kit 0,5Hp | • |
| Drain pump kit 40W | • |
| Reverse osmosis system | - |
| Kit 4 Stainless steel feet 50-70mm | • |
| ADVANCE display | • |
| Kit with 2 Baskets and Stand | • |
| Optional Installabile, Optional not installable | |

C327





