

# C Range

## undercounter


### GLASSWASHER



## C405 ws

### Maidaid **C405 WS** Features

- **2 year warranty**
- Internal regeneration water softener and drain pump as standard
- Four button bright LED display with soft touch controls, twin traffic lights giving instant status updates & operational self-diagnostics



- Alarms menu with hi-level information retrieval
- Quick release parallel wash & rinse arm design
- Surface scrap trays as standard
- Three standard cycle time options with further options available
- Cycle times can be tailored to site requirements
- Automatic self-cleaning at end of service
- Selectable energy saving mode
- Selectable thermostop ensures optimum rinse temperatures
- Patented dual flow wash pump – reducing power consumption whilst retaining wash efficiency
- Moulded wash tank for easy cleaning
- Moulded rack guide giving partial double skin
- Accurate detergent & rinse aid peristaltic dosing pumps as standard



Two 390 x 390mm open cup/glass racks supplied as standard – capable of holding 16 pint glasses.

Additional racks can be purchased at point of order:

**Q902303B**



# C Range

## undercounter

### GLASSWASHER

## C405 ws




### Technical Data

Dimensions (W x D x H)	mm	440 x 540 x 670	Wash tank element	kW	1.4
		+ Feet	Boiler element	kW	2.6
Feet height	mm	5-15	Wash pump	kW	0.18
Rack size	mm	390 x 390	Tank capacity	L	10
Maximum useable height	mm	300	Noise emission	dB	≤ 55
Door opening	mm	320	<b>Packaging Specs</b>		
Theoretical productivity	Racks/h	40	Gross weight	Kg	36
Effective productivity	Racks/h	30*	Cubic volume	m <sup>3</sup>	0.25
			Dim. (W x D x H)	mm	520 x 630 x 830

\*Allowing 30 seconds for reloading  
Cycle times may vary depending on local conditions/services

### Installation Diagram – All services must be within 1 meter





\*Height-adjustable feet + 10mm

### Power Supply

Installed power	AMP	kW
230V – 50Hz – 1N	13*	2.8

\*Supplied with 13A moulded plug and lead

 Pumped waste into upstand, maximum height 700mm

 Power  
 Water supply 2 – 4 bar

### Water Connection

Inlet water pressure	Bar	2 to 4
Flow rate L/Min	L/Min	6
Water inlet temp	°C	10 to 50
Water connection	BSP	¾"
Waste connection	Ø	Int 16.8/ext 21.6

### Cycle Information

Number of standard cycles		3
Standard cycles times	Sec	90/120/150 – adjustable
Special cycle		Plate
Self-cleaning cycle		Full self clean
Water consumption per cycle	L	1.9
Wash temperature	°C	60 – adjustable
Rinse temperature	°C	65 – adjustable