

UG511DSUK



Professional undercounter glasswasher, double skinned, 500 x 500mm basket with integral water softener

Product Family	Dishwashers
Type	Undercounter Glasswasher
Line	TOPLINE
Basket dimensions	500 x 500mm
Outside dimensions (WxDxH)	600 x 600 x 820mm

TECHNICAL SHEET

TECHNICAL DATA



Structure: Double skinned in AISI 304 stainless steel and insulated

Required electrics and fuse protection: 1ph 5.7kW 25A / 3ph 5.7kW 16A / 1ph 4kW 20A / 1ph 2.7kW 13A

Control type: Electronic soft touch controls

WRAS compliant break tank: Yes

Basket dimensions: 500 x 500mm

Baskets per hour: 60 / 40 / 24 / 20

Number of programs: 7

Thermo-acoustic insulation: door and wash chamber

Rinse aid dispenser: Peristaltic pump with electronic adjustment via the control panel

Detergent dispenser: Peristaltic pump with electronic adjustment via the control panel

Useable loading height: 415mm

Wash tank capacity: 11L

Boiler capacity: 6L

Boiler heating element: 5kW 1ph / 5kW 3ph / 3.3kW 1ph / 1.7kW 1ph

Wash tank heating element: 2.0kW

Inlet water maximum temperature: 60°C

Outside dimensions (WxDxH): 600 x 600 x 820mm

Power supply / Total power installed: 230V 1N 50Hz / 5.7kW - 400V 3N 50Hz / 5.7kW - 230V 1N 50Hz / 4.0kW - 230V 1N 50Hz / 2.7kW

Weight (net/gross): 68 / 76kg

Integral continuous water softener: yes

Wash system: Wash pump with 'Soft start' system

Wash pump: 0.7kW

Rinse system: Atmospheric boiler and rinse pump (HTR system)

Drain system: Drain pump and triple stage dynamic filter with partial water exchange in the wash tank

Filtering system: Integral stainless steel top wash tank filter with removable scrap basket with stainless steel micro filter and additional micro filter in the sump for wash pump protection

Water consumption per cycle: 2.7L

Selectable: FRESH WATER function for complete wash tank water replacement after each wash cycle

Selectable: EXTENDED-RINSE function for a prolonged rinse

Balanced and insulated double skinned door with gasket

Thermostat for controlling the rinse water temperature

Self-diagnosis system with fault warning

Insulated boiler

Moulded basket guides

Drain pipe on the boiler for complete drainage

'Stand-by' function of the heating elements during periods of non-use

2 x wash arms in AISI 304 stainless steel

2 x rinse arms in AISI 304 stainless steel

Moulded tank with rounded corners

Connection to water mains with a 3/4 threaded fitting on the back of the appliance

Self cleaning cycle available as standard

Cycle automatically starts when closing the door/hood (optional)

Adjustable feet

ACCESSORIES

[PB50G01](#) - Plastic universal flat-bottomed basket

[WB50G01](#) - Wire fine-mesh flat-bottomed basket

[WB50G03](#) - Wire basket with angled bottom for stem glasses Ø max 72mm

[WB50G04](#) - Wire basket with angled bottom for stem glasses Ø max 120mm

[PHOOS01](#) - Plastic single cutlery basket

[PHOOS02](#) - Plastic cutlery basket with 6 compartments

[PHOOS03](#) - Plastic cutlery basket with 8 compartments

[WSS](#) - Stand for 500 x 500mm basket glasswasher / dishwasher

[KITSONLIV](#) - Retro-fit low level chemical sensor kit for all Topline glass and dishwashers

EQUIPMENT

1 [WB50G01](#) - Wire fine-mesh flat-bottomed basket

1 [WB50G03](#) - Wire basket with angled bottom for stem glasses Ø max 72mm

